

STRIPILED (4FT)

INSTALLATION INSTRUCTIONS



Beghelli Canada
3900 14th Avenue
Markham, Ontario L3R 4R3 Canada
P: (905) 948-9500
F: (905) 948-8673
www.BeghelliCanada.com



Beghelli USA
3250 Corporate Way
Miramar, Florida 33025 USA
P: 800 726 4316 / P: 954 442 6600 F:
954 442 6677
www.BeghelliUSA.com




Beghelli Mexico
Av. Del Marqués No. 70, Int. 4
Parque Industrial Bernardo Quintana
C.P. 76246 El Marqués, Qro.
P: +52 442-221-6439 / F: +52 442-221-6215
www.BeghelliMexico.com

4FT STRIPIED



LOGICA® TITLE 24 DLC OPLE™ LISTED cUL US IP44

Beghelli
LUCE

MODEL INFORMATION



STRIPIED (4FT) LO/MO	
WATTAGE	24W, 40W
VOLTAGE	120-277V, 50/60Hz
WET LOCATION	IP44
OPERATION	HT (AC ONLY)/0-10V DIMMING
WEIGHT	6.2 lbs
DIMENSION	48.0" L X 3.5" W X 3.8" H



CAUTION! ALWAYS MAKE SURE THE POWER IS TURNED OFF before starting installation.

IMPORTANT SAFEGUARDS

When using electrical equipment, basic safety precautions should always be followed including the following:

READ AND FOLLOW ALL SAFETY INSTRUCTIONS.

1. **CAUTION! ALWAYS MAKE SURE THE POWER IS TURNED OFF** before starting installation.
2. Wiring fixture to power supply, shall be performed by a **certified electrician**, and wired in a manner that complies with all local and national electrical codes, as well as the **manufacture's wiring diagram**.
3. Proper replacement of a part removed for user maintenance.

SAVE THESE INSTRUCTIONS!

WARNING ⚠

No user serviceable parts. Refer service to a qualified service technician. Read instructions prior to installing and/or operating this device. Installation should be performed by a licensed electrician/installer in accordance with local codes.


Beghelli
LUCE

DIMMING WIRING DIAGRAM

- 0-10V dimming wires must be run from a different conduit out of the J-box.

0-10V LEAD


VIOLET.....(DIM +)
GRAY.....(DIM -)




AC LEADS

BLACK..... (HOT)
WHITE.....(NEUTRAL)
GREEN..... (GROUND)


INSTALLATION




Engage taps
& slide to lock




- Measure, locate fixture's position, and mark locations for the mounting hole.
- Install anchors and screws to ceiling as shown below.
(HARDWARE BY OTHERS).
- Install Cover Plates as shown on the right.




SURFACE MOUNT (SM)




1. Leave approxi. 5/32" space between screw and ceiling/wall surface.
2. Guild the fixture, so that the screw's head inside the housing, and slide sideways to lock fixture in place (as shown).




AVIATION CABLE KIT (AC)



1. Feed cables thru gliders as shown.
2. Hook the clips thru the loop of the cable as shown.
3. Hook the assemblies to fixture as shown.



CHAING HANG KIT (CH)



1. Feed chain thru hook clip as shown.
2. Hook the assemblies to fixture as shown.

