



NYC-STX-C



■ ■ ■ features + benefits

NEW YORK CITY APPROVED	<ul style="list-style-type: none"> • 8" high red lettering with 1" stroke • 100' viewing distance • 15' on-center spacing with 3' egress
REMOTE CAPABLE	<ul style="list-style-type: none"> • 2 or 3 fully adjustable 1.5W, glare-free LED lamp heads • Twist locking collar for securely holding lamp position • Top and side knockout for lamp head installation
OPERATING TEMPERATURE	<ul style="list-style-type: none"> • 68°F up to 122°F (20°C up to 50°C)
DURABLE CONSTRUCTION	<ul style="list-style-type: none"> • 20 gauge steel frame • High-impact thermoplastic remote heads
LED DESIGN	<ul style="list-style-type: none"> • High-output, high-efficiency LEDs • External LED status indicator and push button test switch
UL LISTED	<ul style="list-style-type: none"> • Dry location
MULTIPLE MOUNTING OPTIONS	<ul style="list-style-type: none"> • Universal backplate knockouts • Side and top mount canopy
90 MINUTE EMERGENCY LIGHT	<ul style="list-style-type: none"> • 9.6V rechargeable nickel cadmium (Ni-Cad) battery • Automatic, solid-state 24-hr battery recharge